

10/04/00



HEWLETT-PACKARD COMPANY
Intellectual Property Administration
P. O. Box 272400
Fort Collins, Colorado 80527-2400

10-10-00

PATENT APPLICATION **A**

ATTORNEY DOCKET NO. 10002222-1

IN THE U.S. PATENT AND TRADEMARK OFFICE
Patent Application Transmittal Letter

COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing under 37 CFR 1.53(b) is a(n): ☒ Utility ☐ Design☒ original patent application,☐ continuation-in-part application

JC953 U.S. PTO
09/680545
10/04/00

INVENTOR(S): Gordon Margulieux

TITLE: Persistent Emulated Data Storage Using Dedicated Storage In A Target Mode Disk Emulator

Enclosed are:

☒ The Declaration and Power of Attorney. ☒ signed ☐ unsigned or partially signed☒ 2 sheets of drawings (one set) ☐ Associate Power of Attorney☐ Form PTO-1449 ☐ Information Disclosure Statement and Form PTO-1449☐ Priority document(s) ☐ (Other) _____ (fee \$ _____)

CLAIMS AS FILED BY OTHER THAN A SMALL ENTITY				
(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) TOTALS
TOTAL CLAIMS	20 — 20	0	X \$18	\$ 0
INDEPENDENT CLAIMS	3 — 3	0	X \$80	\$ 0
ANY MULTIPLE DEPENDENT CLAIMS	0		\$270	\$ 0
BASIC FEE: Design (\$320.00); Utility (\$710.00)				\$ 710
TOTAL FILING FEE				\$ 710
OTHER FEES				\$
TOTAL CHARGES TO DEPOSIT ACCOUNT				\$ 710

Charge \$ 710 to Deposit Account 08-2025. At any time during the pendency of this application, please charge any fees required or credit any over payment to Deposit Account 08-2025 pursuant to 37 CFR 1.25. Additionally please charge any fees to Deposit Account 08-2025 under 37 CFR 1.16, 1.17, 1.19, 1.20 and 1.21. A duplicate copy of this sheet is enclosed.

"Express Mail" label no. EH862486010USDate of Deposit 10-4-00

I hereby certify that this is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Commissioner for Patents, Washington, D.C. 20231.

By Chris Griffin
Typed Name: Chris Griffin

Respectfully submitted,

Gordon Margulieux

By Steven R. Ormiston

Steven R. Ormiston

Attorney/Agent for Applicant(s)

Reg. No. 35,974

Date: 10/3/00

Telephone No.: (208) 396-2544

"Express Mail" mailing label number: EH862486010US

Date of Deposit: 10-4-00

I hereby certify that this paper or fee is being deposited with the United States Postal Service

"Express Mail Post Office to Addressee" services under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Typed Name of Person Mailing Paper or Fee: Chris Griffin

Signature: Chris Griffin

PATENT APPLICATION
DOCKET NO. 10002222-1

**PERSISTENT EMULATED DATA STORAGE USING DEDICATED
STORAGE IN A TARGET MODE DISK EMULATOR**

INVENTOR:

Gordon Margulieux

**PERSISTENT EMULATED DATA STORAGE USING DEDICATED STORAGE IN A
TARGET MODE DISK EMULATOR**

RELATED APPLICATIONS

The present application is related to pending, commonly assigned, and concurrently filed U.S. Patent Application Serial No. Attorney Docket No. 10002221-1 entitled "EMULATION OF DYNAMICALLY RECONFIGURABLE COMPUTER SYSTEM," which is hereby incorporated herein by reference.

TECHNICAL FIELD

The present invention relates in general to emulation of computer peripheral devices and, in particular, to emulating persistent storage of data in peripheral devices having data storage capabilities.

BACKGROUND

When constructing data processing or communication equipment, it is generally desirable to emulate the operation of various components and the interaction of these components with each other before all such components are available for actual physical testing. Such emulation generally enables the identification of potential fault conditions to be identified and the exercise of software within host devices designed to identify and respond to fault conditions originating within peripheral or other devices. In addition to enabling testing of system components by emulating such components, emulators generally enable the testing of diagnostic features of a computer system by deliberately injecting invalid data into the system to prompt for a response by diagnostic elements of a computer system.

Emulation is commonly accomplished through the use of an emulating computer connected to a computer system under test. Various components of the computer under test may be emulated by the emulating computer which may be coupled to the computer under test employing standard communication mechanisms. One such component is that of data storage, and in particular, non-volatile data storage. Generally, emulation of non-volatile computer storage computer storage is accomplished by employing data storage equipment already employed for the ongoing operation of the emulating computer. In this case however, the emulated data storage operations compete for resources, within the emulating device, with the data storage requirements of the emulating computer's operating system, thereby limiting the effectiveness of this approach to data storage emulation.

FIGURE 1 is a block diagram 100 depicting a system for emulating host device data storage equipment according to a prior art solution. It may be seen that host device 101 communicates with conventional emulator 102 via communication line 104. Internal shared storage 103 is the storage available for emulation in the system of FIGURE 1. Generally, internal shared storage is provided by standard non-volatile computer storage equipment, such as a hard disk drive. Generally, emulator 102, which may be a general purpose computer, uses storage 103 for its own purposes, including storage of its own operating system, application programs, log files, and other miscellaneous data. Accordingly, any use

of shared storage 103 for the purpose of emulating host device storage equipment must generally compete with the above-stated needs of emulator 102, thereby limiting the resources available for emulation purposes.

Generally, at the conclusion of each emulation operation, the data stored in an appropriately designated portion of the shared memory 103 is reset in preparation for a subsequent emulation operation. Accordingly, any emulation related data stored in the shared memory is generally lost once a particular emulation session has concluded. Thereafter, if the host device wishes to emulate a return to the storage device which was previously emulated, all data associated the previous emulation operation will have generally been deleted, thereby defeating an ability to emulate a normal resumption of interaction of the host device with the first storage device, after having accessed one or more other storage devices.

In addition, the sharing of data storage resources in prior art systems tends to make it difficult to determine in advance how much data in shared storage 103 is available for host device storage device emulation. Moreover, the sharing of the available capacity in shared resource 103 will generally prevent the emulation process from employing the full capacity of shared resource 103 for emulation purposes. Accordingly, the emulation of host device 101 storage devices will generally be limited to storage equipment of modest storage capacity in order to abide by the limitations imposed the need to share resources with emulator 102.

Accordingly, it is a problem in the art that storage resources employed for emulating host device storage equipment are generally shared with equipment employed for emulating logical operation of the host device storage equipment.

It is a further problem in the art that emulation data stored during an initial emulation session is generally reset upon conclusion of the initial session, thereby preventing emulation of a normal resumption of access to an actual host device storage device.

It is a still further problem in the art that the sharing of data storage resources with emulation equipment generally limits the data storage capacity of equipment which may be emulated employing the systems of the prior art.

SUMMARY OF THE INVENTION

The present invention is directed to a system and method which provides persistent non-volatile dedicated emulated storage for enabling emulation of storage equipment which may be intermittently accessed and cycled through various power conditions. The inventive approach preferably dedicates at least one emulating storage device to the emulation of a storage device to be emulated, wherein the dedicated storage device is enabled to provide data storage which remains intact through one or more different emulation operations conducted by an emulator to which the dedicated component is coupled, and one or more possible power cycling operations of the emulated storage device.

In a preferred embodiment, the dedicated device(s) coupled to the emulator to enable more realistic storage device emulation may be a hard disk drive, magneto optic device, tape drive, CD-RW (read-write compact disk), or other non-volatile storage mechanism. Although the emulating device need not be the same as the emulated device (the device native to the host computer), there is generally some advantage in having the characteristics of the two devices approximate one another. For example, when emulating the operation of a 10 megabyte disk drive, use of a disk drive with a capacity approaching 10 megabytes and having other operating characteristics in common with the emulated device will generally provide for a more accurate emulation process.

In a preferred embodiment, the deployment of an emulator, which may be a general purpose computer, as an intermediary device between a host device and one or more emulating devices preferably enables a more seamless emulation process than an arrangement in which the emulating devices are directly coupled to the host device or other external device. Disposing an emulator in between a host device and one or more emulating devices preferably enables the host device to interact seamlessly with the emulating devices. The emulator preferably provides convenient means for transferring control data and storage data from the host device to the one or more emulating storage devices. Moreover, the deployment of an emulator preferably enables a host device, communicating along a single communication line with an emulator, to interact with a substantial number of emulated storage devices.

Accordingly, it is an advantage of a preferred embodiment of the present invention that data stored employing a dedicated emulating storage device will be preserved after emulated power cycling of the storage device being emulated.

It is a further advantage of a preferred embodiment of the present invention that a dedicated storage device coupled to an emulator may be selected and configured so as to enable highly accurate approximation of the characteristics of the device being emulated.

It is a still further advantage of a preferred embodiment of the present invention that a dedicated storage device having a storage capacity closely approximating that of the device being emulated may be selected.

It is a still further advantage of a preferred embodiment of the present invention that the resources available to an emulating dedicated storage device are generally independent of the storage space needed to service the needs of the emulating computer.

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present invention.

BRIEF DESCRIPTION OF THE DRAWING

For a more complete understanding of the present invention, reference is now made to the following descriptions taken in conjunction with the accompanying drawing, in which:

FIGURE 1 is a block diagram depicting a system for emulating host device data storage equipment according to a prior art solution;

5 FIGURE 2 depicts a system for conducting storage device emulation employing dedicated storage equipment according to a preferred embodiment of the present invention;

FIGURE 3 depicts the system for storage device emulation of FIGURE 2 in greater detail according to a preferred embodiment of the present invention;

FIGURE 4 depicts the system for storage device emulation of FIGURE 3 employing a modified host bus adaptor port implementation according to a preferred embodiment of the present invention; and

FIGURE 5 depicts computer apparatus adaptable for use with the present invention.

DETAILED DESCRIPTION

FIGURE 2 depicts a system 200 for conducting storage device emulation employing dedicated storage equipment according to a preferred embodiment of the present invention.

In a preferred embodiment, emulator 201 employs internal system storage 202 substantially exclusively for the operating system, application programs, and data associated with the operation of emulator or emulating computer 201 and not for emulating host device storage. Emulation of host device storage operations is preferably provided by external dedicated storage components 204-1 and 204-2. As FIGURE 2 indicates, an essentially unlimited number of external dedicated storage devices may be connected to emulator 201, as shown by the dots leading up to non-volatile external dedicated storage device N 204-N.

In a preferred embodiment, the storage components dedicated to emulation of host device 101 storage activity are not limited to being disposed externally to emulator 201. Optionally, internal non-volatile dedicated storage device 203 may be deployed internal to emulator 201 and operate in substantially the same manner as devices 204-1 to 204-N. Thus, in the embodiment depicted in FIGURE 2, the storage operations specific to the operation of emulator 201 and those dedicated to emulation of host device 101 storage activity are preferably distributed among separate physical components. Such segregation of activity preferably enables the various dedicated storage devices, whether internal or external, to operate free of the constraints imposed by the prior art storage sharing system depicted in FIGURE 1.

In a preferred embodiment, the dedicated storage devices 203 and 204-1 to 204-N may be selected so as to best match the host device storage devices they are intended to emulate. Alternatively, a substantially generic set of dedicated storage devices 203 and 204-1 to 204-N may be selected and configured in software to emulate, as accurately as possible, the storage devices to be deployed with host device 101.

In a preferred embodiment, emulator 201 coordinates the communication of control information, storage data, and optionally, power supply information between host device 101 and the dedicated storage devices. Control information preferably indicates a destination for

storage data transmitted from host device 101 toward emulator 201, and alternatively, a source of retrieved storage information directed from emulator 201 toward host device 101.

In an exemplary sequence of events, host device 101 may interact with dedicated storage device 1 201-1 and leave data therein, and then operate to retrieve data from another device, such as dedicated storage device 203. Upon regaining access to external dedicated storage device 204-1, the data left therein when the host device 101 was previously in communication therewith, will preferably be preserved unchanged. In this manner, the present invention provides for more realistic emulation than would have been possible employing the prior art "shared storage" where data would be erased by switching from emulation of one storage device to another by an emulator reset operation. In the embodiment of FIGURE 2, emulator 201 enables the host device to successively access a sequence of different emulating storage devices, while each of the emulating storage devices preserves data stored therein between successive emulation sessions with the host.

FIGURE 3 depicts a typical target mode emulator program within a high availability storage system. Host controller 301 is generally a subset of host device 101 depicted in FIGURE 2. In a preferred embodiment, the upper portion of the FIGURE represents components of host computer. The host computer preferably includes host controller 301 that is attached to a host BUS adapter 302 (HBA) which preferably coordinates communication with the emulator 304. The host computer also preferably includes non-emulated dedicated storage devices 303-1 to 303-N which preferably remain operative and under the control of host controller 301. Generally, the emulation process will involve emulating one of the non-emulated dedicated storage devices 303-1 to 303-N (storage devices native to the host computer system) at a time employing one or more of the non-volatile dedicated emulator storage devices 308-1 to 308-N.

In a preferred embodiment, emulator 304, which preferably includes emulator data interface port 306, is coupled to the controller HBA 302. Within emulator 304, command and control processing 305 preferably coordinates communication between emulator data interface port 306 and internal host bus adaptor (HBA) ports 307-1 to 307-N. Although the embodiment of FIGURE 3 depicts a deployment of one HBA port for each non-volatile

dedicated storage device, in an alternative embodiment, a single HBA port may be deployed to interface with all deployed non-volatile emulator storage devices. Such an alternative embodiment is shown in FIGURE 4.

In a preferred embodiment, host controller 301 is a custom board which forms a portion of a larger computer system. Preferably, where a custom board is deployed, this board would be configured for interacting with and controlling a plurality of data storage devices. Alternatively, the host controller 301 could be any computer system. Similarly, the emulator 304 is preferably a personal computer, but alternatively could be any computer system.

Non-volatile dedicated emulator storage devices 308-1 to 308-N could be dedicated hard disk drives coupled to emulator 304. Alternatively, dedicated storage devices 308-1 to 308-N could any other form of non-volatile storage equipment including but not limited to tape drives, magneto-optic devices, and CD-RW (readable, writeable compact disk drives). The dedicated storage devices may be disposed externally to the emulator 304 or within an enclosure also housing emulator 304.

In a preferred embodiment, the emulator storage devices may be selected so as to most accurately reflect the operating characteristics of the device being emulated. Employing this approach, the emulating device should accurately approximate the behavior of the device being emulated. Alternatively, emulating devices whose characteristics vary in selected respects from the device being emulated may be selected in order to deliberately cause selected errors and/or exception conditions to occur. In this manner, the response of diagnostic code within the host controller 301 may be exercised with greater frequency than where the emulating device and emulated device are highly similar. By varying the functional disparity between the emulated and emulating devices in successive emulation operations, the inventive approach may be effective in exercising a considerable range of diagnostic code functions, thereby enabling a more complete examination of the operation of the diagnostic code within host controller 302.

FIGURE 5 depicts computer apparatus adaptable for use with a preferred embodiment of the present invention. FIGURE 5 illustrates computer system 500 adaptable

for use with a preferred embodiment of the present invention. Central processing unit (CPU) 501 is coupled to system bus 502. The CPU 501 may be any general purpose CPU, such as an HP PA-8200. However, the present invention is not restricted by the architecture of CPU 501 as long as CPU 501 supports the inventive operations as described herein. Bus 502 is coupled to random access memory (RAM) 503, which may be SRAM, DRAM, or SDRAM. ROM 504 is also coupled to bus 502, which may be PROM, EPROM, or EEPROM. RAM 503 and ROM 504 hold user and system data and programs as is well known in the art.

The bus 502 is also coupled to input/output (I/O) adapter 505, communications adapter card 511, user interface adapter 508, and display adapter 509. The I/O adapter 505 connects to storage devices 506, such as one or more of hard drive, CD drive, floppy disk drive, tape drive, to the computer system. Communications adapter 511 is adapted to couple the computer system 500 to a network 512, which may be one or more of local (LAN), wide-area (WAN), Ethernet or Internet network. User interface adapter 508 couples user input devices, such as keyboard 513 and pointing device 507, to the computer system 500. The display adapter 509 is driven by CPU 501 to control the display on display device 510.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

WHAT IS CLAIMED IS:

1 1. A system for providing accurate data storage emulation in a computer system,
2 the system comprising:

3 a host computer system having at least one storage system;

4 an emulating computer in communication with said host computer system; and

5 an emulating storage system in communication with said emulating computer
6 dedicated to emulation of an operation of at least one of said at least one storage systems.

1 2. The system of claim 1 wherein said emulating storage system is disposed
2 within an enclosure housing said emulating computer.

1 3. The system of claim 1 wherein said emulating storage system is located
2 externally to an enclosure housing said emulating computer.

1 4. The system of claim 1 further comprising:

2 at least one additional emulating storage system.

1 5. The system of claim 1 wherein said emulating storage system includes
2 operating characteristics substantially approximating operating characteristics of said at least
3 one storage system of said host computer.

1 6. The system of claim 1 further comprising:

2 means for preserving data stored in said emulating storage system during emulated
3 power cycling of said emulating storage system.

1 7. The system of claim 1 wherein said at least one storage system comprises:

2 a hard disk drive having a storage capacity; and

3 said emulating storage system comprises:

4 a hard disk drive having a storage capacity substantially equal to said storage
5 capacity of said hard disk drive.

1 8. The system of claim 1 wherein said emulated storage system substantially
2 excludes data pertaining to internal operation of said emulating computer.

1 9. A method for accurately emulating host computer data storage, the method
2 comprising the steps of:

3 providing a host computer system capable of interacting with at least one storage
4 system native to said host computer system;

5 disposing an emulating computer in communication with said provided host computer
6 system;

7 coupling an emulating storage system to said disposed emulating computer; and

8 dedicating said coupled emulating storage system to emulation of said at least one
9 storage system native to said host computer system.

1 10. The method of claim 9 further comprising the step of:

2 excluding data associated with an internal operation of said emulating computer from
3 said dedicated coupled emulating storage system.

1 11. The method of claim 9 further comprising the step of:
2 disposing said coupled emulating storage system within an enclosure housing said
3 emulating computer.

1 12. The method of claim 9 further comprising the step of:
2 disposing said coupled emulating storage system outside an enclosure housing said
3 emulating computer.

1 13. The method of claim 9 further comprising the step of:
2 dedicating each of a plurality of emulating storage devices to a separate one of said at
3 least one storage devices native to said host computer system.

1 14. The method of claim 13 further comprising the step of:
2 emulating a succession of said at least one storage device native to said host computer
3 system employing a succession of said plurality of dedicated emulating storage devices.

1 15. The method of claim 14 further comprising the step of:
2 preserving data stored in said plurality of dedicated emulating storage devices while
3 said succession of said at least one storage devices native to said host computer system is
4 emulated.

1 16. A system for emulating an operation of at least one storage device adapted for
2 operation with a host computer system, the system comprising:

3 means for dedicating an emulating storage device to each of said at least one storage
4 devices adapted for operation with said host computer system, thereby establishing at least
5 one dedicated emulating storage device;

6 means for coupling said at least one dedicated emulating storage device to said host
7 computer via an intelligent interface; and

8 means for monitoring an operation of said at least one dedicated emulating storage
9 device.

1 17. The system of claim 16 wherein said monitoring means comprises:

2 means for diagnosing a fault condition among said at least one dedicated emulating
3 storage devices.

1 18. The system of claim 17 wherein said monitoring means further comprises:

2 means for performing diagnostic operations in response to said diagnosed fault
3 condition.

1 19. The system of claim 16 wherein said means for dedicating comprises:

2 selecting said at least one dedicated emulating storage device having operating
3 characteristics substantially approximating operating characteristics of said at least one
4 storage device adapted for operation with said host computer system.

1 20. The system of claim 16 wherein said intelligent interface is a computer.

**PERSISTENT EMULATED DATA STORAGE USING DEDICATED
STORAGE IN A TARGET MODE DISK EMULATOR**

ABSTRACT OF THE DISCLOSURE

The present invention relates to a system and method for emulating the operation of storage devices deployed in a host computer system. The inventive approach preferably involves the use of an emulator employing storage space and equipment specifically allocated for the emulation of particular storage devices associated with the host computer. Emulating storage devices preferably preserve their data through various possible power cycling operations of the emulated devices. The emulating or emulator devices may generally be disposed inside or outside of the emulator housing.

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500

FIG. 1




FIG. 2




FIG. 5




FIG. 3





FIG. 4



DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONATTORNEY DOCKET NO. 10002222-1

As a below named inventor, I hereby declare that:

My residence/post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Persistent Emulated Data Storage Using Dedicated Storage In A Target Mode Disk Emulator

the specification of which is attached hereto unless the following box is checked:

() was filed on _____ as US Application Serial No. or PCT International Application Number _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understood the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose all information which is material to patentability as defined in 37 CFR 1.56.

Foreign Application(s) and/or Claim of Foreign Priority

I hereby claim foreign priority benefits under Title 35, United States Code Section 119 of any foreign application(s) for patent or inventor(s) certificate listed below and have also identified below any foreign application for patent or inventor(s) certificate having a filing date before that of the application on which priority is claimed:

COUNTRY	APPLICATION NUMBER	DATE FILED	PRIORITY CLAIMED UNDER 35 U.S.C. 119
			YES: _____ NO: _____
			YES: _____ NO: _____

Provisional Application

I hereby claim the benefit under Title 35, United States Code Section 119(e) of any United States provisional application(s) listed below:

APPLICATION SERIAL NUMBER	FILING DATE

U. S. Priority Claim

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION SERIAL NUMBER	FILING DATE	STATUS (patented/pending/abandoned)

POWER OF ATTORNEY:


As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Customer Number 022879Place Customer
Number Bar Code
Label hereSend Correspondence to:
HEWLETT-PACKARD COMPANY
Intellectual Property Administration
P.O. Box 272400
Fort Collins, Colorado 80528-9599

Direct Telephone Calls To:

Steven R. Ormiston
(208) 396-2544

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Inventor: Gordon MargulieuxCitizenship: USResidence: 2040 Interlachen Way, Meridian, ID 83642Post Office Address: Same as Residence

 Inventor's Signature

9-20-2000
 Date